



**Ignition Switch Assembly**



**BCM/Fuse Box**




**Códigos de error de programación de LED**

El LED del módulo parpadea en ROJO durante la programación

- 1x ROJO = No se puede comunicar con RFID o datos del inmovilizador.
- 2x ROJO = Sin actividad CAN. Compruebe las conexiones de los cables CAN.
- 3x ROJO = No se detectó ignición. Verifique la conexión del cable de encendido y CAN.
- 4x ROJO = Diodo de salida de encendido requerido no detectado.

## CARTRIDGE INSTALLATION



**1** Slide cartridge into unit. Notice button under LED.

**2**

Ready for Module Programming Procedure.

## MODULE PROGRAMMING PROCEDURE



**1** For this installation, the Weblink HUB is required.



**2** Remove OEM key 1 from keychain.




Place all other keyfobs at least 1 foot away from the Weblink HUB. Failure to comply may result in damage to other keyfobs or interfere with the keyfob reading process.




**3** Flash the module using the Weblink HUB. Follow the on screen instructions to complete the keyfob reading process.

**4**




**WARNING:**  
Do not press the module programming button. Connect power first. Connect module to vehicle.

**5**




Using OEM key 1, turn key to ON position.

**6**



Wait, LED will turn solid BLUE for 2 seconds

**7**



Turn key to OFF position.

**8**

Module Programming Procedure completed.